





Α	1° 6° (0.46M)	6" (0.46M) BOW EYE TO FWD GUNNEL W/RUB-RAIL				
В	2° 13/4°° (0.65M)	BOW EYE TO KEEL				
С	1' 61/2" (0.47M)	STERN EYE TO KEEL				
D	16' 71/4" (5.06M)	AFT KEEL POINT TO BOW EYE				
E	20'0" (6.10M)	MOLDED SWIM PLATFORM TO FWD GUNNEL W/RUB-RAIL AT CENTERLINE				
F	0° 113/8°° (0.29M)	CHINE TO KEEL (LOWEST POINT WHEN BOAT IS LEVEL)				
G	6' 83/8" (2.04M)	CHINE TO CHINE				
Н	8° 4°° (2.54M)	BEAM W/RUB-RAIL				
I	1° 03/4° (0.32M)	KEEL TO INBOARD STRAKE				
J	2" 25/8" (0.68M)	KEEL TO OUTBOARD STRAKE				

20°	DEADRISE		
3100 lbs./1406 kg.	DRY WEIGHT OF STANDARD BOAT		
3350 lbs./1520 kg.	MAX TRAILERING WEIGHT OF BOAT WITH HEAVIEST ENGINE, FULL FUEL <i>(NOT INCLUDING</i> <i>GEAR)</i>		



TITLE:										
TRAILER Q.C. DIMENSIONS										
DRAWING NUMBER:	SHE	ET:				SCALE:				
1055-002-025 1 0		F 1				N.T.S.				
DRAWN BY:	DATE:	CH	ECKED BY	DATE: A P	proved 8/31/17	DATE:				
TLH	8/29/17			Aþ	proved 6/3 1/17					